

BUCKINGHAM MFG.

P/N 7002 / 7003 Dual Rescue Strap Instructions

Warning: Do not use this product if you cannot understand and follow the instructions and warnings that come with it and complete all necessary functions.

Buckingham's Dual Rescue Strap (P/N 7002 / 7003) enables the user to safely and easily rescue a co-worker from an elevated position using the 101 SR Self-Rescue System. The Dual Rescue Strap (P/N 7002 / 7003) must not be used for any other purpose.

Read carefully, understand, and heed these and all related product instructions, warnings, and cautions before using this equipment. Failure to do so could result in serious injury or death. This equipment is intended for use by properly trained professionals only.

USE INSTRUCTIONS FOR HURT-MAN RESCUE, USING THE DUAL RESCUE STRAP & 101SR SELF-RESCUE SYSTEM.

- Remove the descender with pre-rigged 1/2" rope and attached locking snap hook from the storage bag and connect the snap hook to a suitable anchor point.
- Connect the Dual Rescue Strap to the descender with the 1st. Carabiner, use the second carabiner to attach the Dual Rescue strap to a suitable attachment point on your harness as shown in figure 1.
- Rappel down to a height slightly above the victim, attach the third carabiner to a suitable attachment point on the victim. (See Fig. 2)
- Adjust the friction buckle on the Dual Rescue Strap taking up the slack between the victim and the Dual Rescue Strap. Ensure as much slack is taken up as possible.
- When all slack is taken up cut the victim's fall arrest lanyard. (see Fig. 3) (Note slack must be taken up so that no part of the system sees impact loading).
- Once the victim is being supported solely by the 1/2" diameter rope, descender and the Dual Rescue System lower the victim to safety at a controlled rate of speed by squeezing the handle with one hand while using the other hand to control the free end of the rope. (See Fig 4)



NOTES: Rescue Buck P/N 694 (simulated training victim) shown in above photos.
PN 7002 shown in above photos.
Hardware, color, lengths may vary from that shown.

STATEMENT of OBSOLESCENCE:

Precise “useful life expectancy” or “shelf life” for this product is not specified, as the degree of use, conditions of use, and the degree of care and storage determines useful life. All users maintain responsibility to select proper equipment for the job, be properly trained in its use, and ensure all personnel support equipment passes inspection before each use. Upon evidence of defects, damage or deterioration, all equipment shall be removed from service immediately and tagged or marked as unusable or destroyed. Additionally, all equipment shall be inspected on a regular basis not to exceed one year by a Competent Person, as defined by OSHA/ANSI, to verify that the equipment is safe for use. In the event of any question or concern regarding the condition of such equipment, users shall remove the equipment from service for further inspection. All users must comply with OSHA/ANSI/ASTM standards prior to and in using such equipment. For more information regarding safe and appropriate use of equipment, please contact Buckingham Manufacturing at 1-800-937-2825.

INTERNATIONAL USERS:

Notwithstanding the above, please know that certain international jurisdictions require manufacturers of equipment to provide customers with a maximum useful lifespan (sometimes referred to as a “Statement of Obsolescence”). To the extent required, Buckingham personal protective equipment manufactured from synthetic fiber materials including but not limited to items such as webbing and/or rope are subject to a maximum useful lifespan of ten (10) years from the date of manufacture. As stated above proper usage, storage, maintenance, and care impacts the useful lifespan of equipment. Extreme circumstances may require that product must be retired after only one use. This statement is made in conformance and compliance with BS EN 365:2004. International users must ensure that product inspections are completed by Competent Persons as defined by international standards including but not limited to British Standard (“BS”). If equipment fails any inspections, it must be immediately withdrawn from service and destroyed. For more information regarding safe and appropriate use of equipment, please contact Buckingham Manufacturing at 1-800-937-2825.

OUR GUARANTEE:

We guarantee the equipment we manufacture to be free from defects in material and workmanship. We will repair any equipment deemed to be defective which is returned to us by the original purchaser. However, this guarantee is void if any product is changed or altered in any way, or if the product is used in a manner other than for which it is intended. This express guarantee supersedes all other expressed or implied guarantees, obligations or liabilities. There are no implied warranties of merchantability or fitness for a particular purpose and as such, all implied warranties are specifically disclaimed.

LIMITATION ON LIABILITY:

In no event will Buckingham or buyer be liable to the other for lost revenues, lost profits or any other indirect, consequential, special or punitive losses or damages, however caused, whether in action for breach of contract, strict liability, tort, or otherwise, even if advised of the possibility of such losses or damages. In no event will Buckingham’s liability exceed the total amount paid by the buyer to Buckingham for the product or equipment giving rise to such claim(s).

Please see other terms and conditions relating to this product at <https://buckinghammfg.com/terms-conditions/>

REGISTRATION:

Before use of the product, ensure to register and confirm the product at www.buckinghammfg.com/register.

BUCKINGHAM MFG.
Binghamton, NY
(607) 773-2400
www.buckinghammfg.com.